

# **SPECIALTY FITTINGS & INLINE WATER FILTERS**

## **Drain Adapters**



HTM's Inline Drain Adapters can be fitted to the snowgun, water hose or water hydrant to assist in drainage of the hose or snow gun. A drain valve and a ¼ NPT pressure gauge bushing are included, and they can be placed in either port of the adapter.



Female	Male	Part no.	
1½"	1½"	CDA1515DP	
1½"	2"	CDA1520DP	
2"	2"	CDA2020DP	

ALSO AVAILABLE: BSPT, NH & NPSH THREADS

Coupler	Thread	Thread Part no.	
1½"	1½"	CF1515DP	
1½"	2"	CF1520DP	
2"	2"	CF2020DP	

#### **Pressure Test Couplings**



Type MF

**HTM's** Type MF Inline Test Coupling can be installed between the hydrant, hose and snow gun, allowing snowmakers to monitor operating pressures in cases where the hydrant does not have a pressure test port. Use with a standard ¼ NPT pressure gauge, or connect the gauge using *CEJN* high-pressure test fittings.

Description	Part Number	
1½" Male/Female Coupler, ¼" NPT Port	CMF1515G	
2" Male/Female Coupler, 1/4" NPT Port	CMF2020G	

## Inline Water Filters

**HTM's CLF** Series Inline Filters are designed to provide protection to multi-nozzle fan guns and tower guns. The inline filter includes a rugged, heavy duty wedge-wire screen element capable of withstanding pressure differentials of 750 PSI. The screen traps solids outside, so it is easier to clean. Various inlet and outlet configurations are possible with this type of screen.

#### **CLF Filter Housing & CDLF Filter Holder**



- With Female NPSH inlet & Female NPSH outlet.
- Can be attached directly to snow gun or used with HTM Type F & Type B Camlock adapters to suit your application.
- Comes with a 3/8" NPT port for use with flush valve (valve not included)

### **CLS Screen**



- Standard mesh sizes:
  - 30 mesh—0.024" (600 micron) opening
  - 60 mesh—0.010" (250 micron) opening
  - Custom mesh sizes also available

Size	Filter Holder	Filter Housing	Screen 30 Mesh	Screen 60 Mesh
1½"	CDLF15	CLF1515	CLS15-30	CLS15-60
2"	CDLF20	CLF2020	CLS20-30	CLS20-60